

(19) World Intellectual Property Organization
International Bureau




(43) International Publication Date
14 December 2000 (14.12.2000)

PCT

(10) International Publication Number
WO 00/74921 A1

- (51) International Patent Classification⁷: B29C 45/67, F15B 15/14, B30B 1/32
- (21) International Application Number: PCT/EP00/03723
- (22) International Filing Date: 26 April 2000 (26.04.2000)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: PN99A000047 4 June 1999 (04.06.1999) IT
- (71) Applicant (for all designated States except US): SIPA S.P.A. [IT/IT]; Via Caduti del Lavoro, 3, I-31029 Vittorio Veneto (IT).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PAVANETTO, Jader [IT/IT]; Via Isonzo, 10, I-30174 Mestre (IT).
- (74) Agents: GIUGNI, Valter et al.; Propria S.r.l., Via Mazzini, 13, I-33170 Pordenone (IT).
- (81) Designated States (national): BR, JP, US.
- (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE).
- Published: — With international search report.
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: HYDRAULIC PRESS APPARATUS WITH IMPROVED CONTROL OF THE OLEO-DYNAMIC CIRCUIT THEREOF



(57) Abstract: Hydraulic press apparatus with a lower plate (1) and an upper moving plate (2), a hollow cylinder (7) under the lower plate (1), a guide column (10) joined on top to the upper plate (2) and with a lower end portion forming the rod of a piston (13) adapted to slide in the hollow cylinder (7), an aperture (15) in the side surface of the hollow cylinder adapted to connect the inner volume existing above the piston (13) with means (17) that are adapted to apply a hydraulic pressure within said inner volume. The guide column (10) is provided with a cylindrical cavity (18) filled with oil, extending all along the interior of the piston (13) and coming out of the latter from the lower portion thereof. There is provided a plunger-type piston that is arranged to slide within said cylindrical cavity and is provided with an upper cylindrical portion (20) that plugs said inner cavity, and with a lower portion (21) having a smaller diameter. A through-bore (22) connects the inner cylindrical cavity (18) with said inner volume (16) when the upper cylindrical portion (20) of the plunger-type piston is displaced under the level of said through-bore.

WO 00/74921 A1